

**Product Function**

Measurement of AC leakage current, AC current.

**Product features**

1. The iron core is made with high performance material and digital integration technology, small volume, high accuracy.
2. Adopts magnetic shielding technology, almost unaffected by the external magnetic field, strong anti-interference ability.
3. Peak hold function. Data storage function.

**Technical Specification**

<b>Power Supply</b>	DC3V Alkaline dry battery LR03 X 2PCS
<b>Range</b>	0.00mA~300.0A
<b>Resolution</b>	10uA
<b>Measurement Accuracy</b>	±1.5%±5dgt (23°C±3°C, below 70%RH)
<b>Meter Weight</b>	0.31kg (include accessories)
<b>Meter Dimension</b>	180mmX72mmX32mm
<b>CT Size</b>	Φ 40mm
<b>LCD Size</b>	35mmX21.5mm; display area: 32mmX15mm
<b>Sampling Rate</b>	2 times/second
<b>Frequency</b>	50Hz, 60Hz Automatic identification
<b>Data Store</b>	99 groups , flash display "FULL" symbol indicate stored full
<b>Peak Hold</b>	Peak capture and hold function, long press <b>HOLD</b> key display peak value
<b>Data Hold</b>	Data hold function: "DH" symbol display
<b>Overflow Display</b>	Exceed measure range overflow function: "OL" symbol display
<b>Automatic Shut Down</b>	5 Minutes after power on, will shut down automatically without any operation to reduce the power consumption.
<b>Battery Voltage</b>	When battery voltage lower than 2.8V, will display low battery voltage symbol "⚡", remind to replace battery
<b>Working Current</b>	5mA
<b>Line Voltage</b>	Below AC 600V circuit measurement
<b>Shift</b>	Automatically
<b>Accessories</b>	Meter: 1PCS; Tool bag: 1PCS; LR03 Alkaline battery : 2PCS